



20
YEAR
WARRANTY

Product Installation Floor/Surface

DEVIheat™ 150S DEVIheat™ Mirror 150S

DEVIheat™ is a high-quality, braided screen, self-adhesive all-in-one mat with FEP insulated conductors and a red PVDF outer sheath (non UV stable). The round profile, very low height (only 2.5 mm) and robust construction ensures a fast, simple and safe installation perfect for renovating existing floors.

DEVIheat™ Mirror 150S heating mat is used for keeping the bathroom mirror mist free by mounting the heating mat in the adhesive behind the mirror.

The two cold leads have clearly visible connections to avoid accidentally installing the heated cable in the wall.

To ensure a long life-time, all cables are minutely inspected including tests for Ohmic resistance, high voltage and material controls to ensure the quality. This means that we are proud to supply our full floor extended DEVIwarranty™.

Benefits:

- Fast and easy to install
- Self-adhesive mesh
- Very low height - only 2.5 mm
- Long life-time

Standard compliance:

- IEC60335-2-96

Approvals:



Type	Value
Nominal voltage	230 V~
Construction	Round, single conductor with screen, two cold leads
Output	150 W/m ² @ 230 V~
Max. permissible use temperature, powered	110 °C
Max. permissible use temperature, unpowered	120 °C
Cable thickness	2.5 mm
Deformation strength	600 N
Pulling strength	120 N
Conductor insulation	FEP
Outer sheath	PVDF
Screen	10 x CU threads
Cold lead	2 x 3 m DSWB, 1 x 1,0 mm ² , with screen
Min. installation temperature	-5 °C
Bending Ø, min.	6 x cable diameter
IP Class	IPX7
Set with flexpipe	Flexpipe, inner ø6,7 mm, outer ø10 mm, 2,5 m, Black

Types: set DEVIheat™ 150S + Flexpipe

Item no.	Output @ 230V~	Dimensions (W x L)	Heated area	Resistance	EAN no.
140F0328	75 W	0,5 x 1 m	0,5 m ²	705 Ω	5703466202777
140F0329	150 W	0,5 x 2 m	1,0 m ²	353 Ω	5703466202784
140F0330	225 W	0,5 x 3 m	1,5 m ²	235 Ω	5703466202791
140F0331	300 W	0,5 x 4 m	2,0 m ²	176 Ω	5703466202807
140F0332	375 W	0,5 x 5 m	2,5 m ²	141 Ω	5703466202814
140F0333	450 W	0,5 x 6 m	3,0 m ²	118 Ω	5703466202821
140F0334	525 W	0,5 x 7 m	3,5 m ²	101 Ω	5703466202838
140F0335	600 W	0,5 x 8 m	4,0 m ²	88 Ω	5703466202845
140F0336	750 W	0,5 x 10 m	5,0 m ²	74 Ω	5703466202852
140F0338	900 W	0,5 x 12 m	6,0 m ²	59 Ω	5703466202876
140F0339	1050 W	0,5 x 14 m	7,0 m ²	50 Ω	5703466202883
140F0340	1200 W	0,5 x 16 m	8,0 m ²	44 Ω	5703466202890
140F0337	1350 W	0,5 x 18 m	9,0 m ²	39 Ω	5703466202869
140F0341	1500 W	0,5 x 20 m	10,0 m ²	35 Ω	5703466202906

Types DEVIheat™ Mirror 150S

Item no.	Output @ 230V~	Dimensions (W x L)	Heated area	Resistance	EAN no.
83000301	50 W	0,5 x 0,7 m	0,35 m ²	1010 Ω	5703466083697
83000300	75 W	0,6 x 0,8 m	0,48 m ²	686 Ω	5703466056660

Types: set DEVIheat™ 150T + Flexpipe + Syntetic nails + DEVIreg™ Opti (140F1055, Pure White, manual: PL)

Item no.	Output @ 230V~	Dimensions (W x L)	Heated area	Resistance	EAN no.
140F1720	150 W	0,5 x 2 m	1,0 m ²	353 Ω	5703466243671
140F1721	225 W	0,5 x 3 m	1,5 m ²	235 Ω	5703466243688
140F1722	300 W	0,5 x 4 m	2,0 m ²	176 Ω	5703466243695
140F1723	375 W	0,5 x 5 m	2,5 m ²	141 Ω	5703466243701
140F1724	450 W	0,5 x 6 m	3,0 m ²	118 Ω	5703466243718
140F1725	600 W	0,5 x 8 m	4,0 m ²	88 Ω	5703466243725
140F1726	750 W	0,5 x 10 m	5,0 m ²	74 Ω	5703466243732
140F1727	900 W	0,5 x 12 m	6,0 m ²	59 Ω	5703466243749
140F1728	1200 W	0,5 x 16 m	8,0 m ²	44 Ω	5703466243756
140F1729	1500 W	0,5 x 20 m	10,0 m ²	35 Ω	5703466243763